


SOD-323



MARKING: C1

200mW SOD-323 Fast Switching Diode

特征 Features

- 开关速度小; Fast Switching Device
- 最大功率耗散 200mW; Power Dissipation of 200mW
- 高稳定性和可靠性。High Stability and High Reliability
- 反向漏电流小。Low reverse leakage

机械数据 Mechanical Data

- 封装: SOD-323 封装 SOD-323 Small Outline Plastic Package
- 极性: 色环端为负极 Polarity: Color band denotes cathode end
- 环氧树脂 UL 易燃等级 Epoxy UL: 94V-0
- 安装位置: 任意 Mounting Position: Any

极限值和温度特性(TA = 25°C 除非另有规定)

Maximum Ratings & Thermal Characteristics (Ratings at 25°C ambient temperature unless otherwise specified.)

参数 Parameters	符号 Symbol	数值 Value	单位 Unit
反向电压 Reverse Voltage	VR	80	V
反向峰值电压 Peak Reverse Voltage	VRM	85	V
功率消耗 Power Dissipation	Pd	200(*)	mW
工作结温 Operating junction temperature	Tj	125	°C
存储温度 Storage temperature range	Ts	-55~+125	°C
平均整流电流 Average Rectified Current	IO	100	mA
正向(不重复)电流 Non-repetitive Peak Forward Current	IFM	200	mA





Valid provided that electrodes are kept at ambient temperature.

(*) Mounted on a glass epoxy circuit board of 20 X 20mm, pad dimension of 4 X 4mm

电特性 Electrical Characteristics (Ratings at 25°C ambient temperature unless otherwise specified).


符号 Symbols	参数 Parameter	测试条件 Test Condition	界限 Limits		单位 Unit
			Min	Max	
IR	反向漏电电流 Reverse Leakage Current	VR1=30V	---	0.1	uA
		VR2=80V		0.5	
VF	正向电压 Forward Voltage	IF=1mA	---	0.62	V
		IF=10mA		0.75	
		IF=100mA		0.98	
Tr _r	反向恢复时间 Reverse Recovery Time	IF= 10mA, VR=6V	---	4	nS
		RL=100Ω			
C	结电容 Capacitance	VR=0.5V, f=1MHZ	---	3	pF

Typical Characteristics



SOD-323 PACKAGE OUTLINE

Plastic surface mounted package



SYMBOL	DIMENSIONS	
	MIN.	MAX.
A		1.000
A1	0.000	0.100
A2	0.800	0.900
b	0.250	0.350
c	0.080	0.150
D	1.200	1.400
E	1.600	1.800
E1	2.500	2.700
L	0.475REF	
L1	0.250	0.400
θ	0°	8°