


SOD-123

400mW SOD-123 Fast Switching Diode



MARKING: 5D

特征 Features

- 开关速度小于 4nS; Fast Switching Device (TRR <4 nS)
- 最大功率耗散 400mW; Power Dissipation of 400mW
- 高稳定性和可靠性。High Stability and High Reliability
- 反向漏电流小。Low reverse leakage

机械数据 Mechanical Data

- 封装: SOD-123 封装 SOD-123 Small Outline Plastic Package
- 极性: 色环端为负极 Polarity: Color band denotes cathode end
- 环氧树脂 UL 易燃等级 Epoxy UL: 94V-0
- 安装位置: 任意 Mounting Position: Any

极限值和温度特性(TA = 25℃ 除非另有规定)

Maximum Ratings & Thermal Characteristics (Ratings at 25℃ ambient temperature unless otherwise specified.)

参数 Parameters	符号 Symbol	数值 Value	单位 Unit
反向电压 Repetitive Reverse Voltage	VRRM	100	V
功率消耗 Power Dissipation	Pd	400	mW
工作结温 Operating junction temperature	Tj	150	℃
存储温度 Storage temperature range	Ts	-65-+150	℃
反向工作电压 Working Inverse Voltage	WIV	75	V
平均整流电流 Average Rectified Forward Current	IF(V)	200	mA
正向(不重复)电流 Non-repetitive Peak Forward Current	IFM	300	mA
正向(不重复)浪涌电流 @tp=1s	IFSM	1.0	A
Peak Forward Surge Current TA=25℃ @tp=1us;		2.0	

Valid provided that electrodes are kept at ambient temperature.

电特性 Electrical Characteristics (Ratings at 25℃ ambient temperature unless otherwise specified.)

符号 Symbols	参数 Parameter	测试条件 Test Condition	界限 Limits		单位 Unit
			Min	Max	
BV	反向击穿电压	IR=100uA	100	---	V
	Breakdown Voltage	IR=5uA	75		
IR	反向漏电流	VR=20V	---	25	nA
	Reverse Leakage Current	VR=75	---	5	uA
VF	正向电压	IF=10mA	---	1.00	V
	Forward Voltage				
TRR	反向恢复时间	IF= 30mA, IR=30mA	---	4	nS
	Reverse Recovery Time	RL=100Ω			
		IRR=3mA			
C	结电容	VR=0V, f=1MHZ	---	4	pF
	Capacitance				

Typical Characteristics

